

## Mineral Oil Light

### Non-stick agent for the application of stone carpets

#### Description

Special non-stick agent for the application of stone carpets.  
Offers smooth application and ideal finish.

#### Fields of application

Used during the application of exterior and interior decorative stone carpets,  
e.g. made of quartz sand and **Neodur® Polyurea** or **Epoxol® 2874**

#### Properties - Advantages

- Facilitates the laying of the resin-mortar, improving the sliding ability of the trowel
- Offers an optimum finish to the stone carpet
- Low odour



#### Packing

5L

#### Technical characteristics

Density (EN ISO 2811-1)	0,84kg/L (±0,05)
-------------------------	------------------

#### Instructions for use

The decorative resin-mortar is poured and applied in one layer on the surface, spreading and pressing it on the substrate by a smooth metal trowel. For the correct and easy application of the stone carpet, it is recommended to wet the trowel with the special non-stick agent **Mineral Oil Light** prior to laying the resin-mortar or pressing it for smoothing. As soon as the trowel begins to become sticky during the application, it is required to re-use **Mineral Oil Light**.

<b>Appearance</b>	Transparent
<b>Packing</b>	5L in plastic pails
<b>Cleaning of tools – Stains removal</b>	By <b>Neotex® 1021</b> immediately after the application. In case of hardened stains, by mechanical means only.
<b>UFI code</b>	70J0-FOX0-J004-TP4V



---

<b>Storage stability</b>	1 year, if kept in the original sealed packaging, protected from frost, humidity and exposure to solar radiation.
--------------------------	---

---

The information supplied in this datasheet, concerning the uses and the applications of the product, is based on the experience and knowledge of NEOTEX® SA. It is offered as a service to designers and contractors to help them find potential solutions. However, as a supplier, NEOTEX® SA does not control the actual use of the product and therefore cannot be held responsible for the results of its use. As a result of continual technical evolution, it is up to our clients to check with our technical department that this present data sheet has not been modified by a more recent edition.

**HEADQUARTERS - PLANT**  
V. Moira str., Xiropigado  
**LOGISTICS SALES & CENTER**  
Loutsas str., Voro

P.O. Box 2315, GR 19600  
Industrial Area Mandra  
Athens, Greece  
T. +30 210 5557579

**NORTHERN GREECE BRANCH**  
Ionias str., GR 57009  
Kalochori, Thessaloniki, Greece  
T. +30 2310 467275