

SIM PANDA PRIMER

Product Name: SIM PANDA PRIMER

Product Description: Water based bituminous emulsion

Application areas : Vertical or horizontal grounds

Application method:

- * the application place should be dry and clean, and should be removed from oil,gasoline & other chemical materials
- * will be mixed with water (1:3 rate), and will be applied brush (400 gr/m²)
- * if the consistence is much intense (thick) then please use hot water to make it thinner. (with % 10-15 rate)
- * after application the color of concrete will be light brown
- * after application clean brush or rolls with hot water
- * After using primer close the cap of the bucket tightly.
- * without opening the cap of the bucket you can keep it in stock for 1 year (between +5 to +30 C)

SPECIFICATIONS	STANDARDS	UNIT	VALUES	TOLERANCE
Density	TS 132	gr/cm ³	1,02	± 0,03
Vaporization waste	TS 132	%	65	± 5
Ash content of waste	TS 132	%	30	± 5
Water content	TS 132	%	55	± 5
Flammability	TS 132		Inflammable	
Drying period	TS 132	Hours	(Max.) 31	
Thermal Flow (100°C)	TS 132		No flow	
Flexibility (0°C)	TS 132		No cracking	
Direct flame test	TS 132		Scorching at place of application	
Water tightness	TS 132		Does not turn back into emulsion	